

AN 1992:196342 CAPLUS

DN 116:196342

ED Entered STN: 16 May 1992

TI Thermosetting glossy topcoating compositions

IN Fukuda, Mitsuhiro; Yabuta, Motoshi; Nakao, Yasushi

PA Kansai Paint Co., Ltd., Japan

SO Jpn. Kokai Tokkyo Koho, 10 pp.

CODEN: JKXXAF

DT Patent

LA Japanese

IC ICM C09D133-14

ICS C09D133-14

CC 42-7 (Coatings, Inks, and Related Products)

FAN.CNT 1

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
------------	------	------	-----------------	------

PI JP 03275780	A2	19911206	JP 1990-74806	19900324
----------------	----	----------	---------------	----------

PRAI JP 1990-74806	19900324			
--------------------	----------	--	--	--

AB The title compns. comprise CO<sub>2</sub>H- and OH group-contg. \*\*\*acrylic\*\*\* resins (OH no. 40-90), epoxy- and OH group-contg. \*\*\*acrylic\*\*\* resins (OH no. 40-90), 5-30% \*\*\*aminoplasts\*\*\*, and quaternary \*\*\*phosphonium\*\*\* salts. Thus, a mixt. of 50% 30:15:15:10:30 Bu \*\*\*methacrylate\*\*\* (I)-2-ethylhexyl \*\*\*acrylate\*\*\* (II)-hydroxyethyl \*\*\*acrylate\*\*\* (III)- \*\*\*methacrylic\*\*\* acid (IV)-styrene (V) copolymer (OH no. 73) soln. 80, 50% 20:18.5:15:30:16.5 I-II-III-V-glycidyl \*\*\*methacrylate\*\*\* (VI) copolymer (OH no. 73) soln. 80, 60% melamine resin 33, Bu<sub>4</sub>P<sup>+</sup> Cl<sup>-</sup> 0.5, UV absorber 1.0, and V-VI- \*\*\*acrylic\*\*\* acid-12-hydroxystearic acid-Me \*\*\*methacrylate\*\*\* graft copolymer \*\*\*microgel\*\*\* 10 parts was coated on primed steel and cured at 140.degree. for 30 min to give a coating with good resistance to acids, water, solvents, gasohol, abrasion, and thermal cycling.

ST \*\*\*aminoplast\*\*\* crosslinker coating; hydroxyethyl \*\*\*methacrylate\*\*\* copolymer coating; glycidyl \*\*\*methacrylate\*\*\* copolymer coating; \*\*\*acrylate\*\*\* copolymer coating; \*\*\*methacrylic\*\*\* acid copolymer coating; styrene copolymer coating

IT Coating materials

( \*\*\*acrylic\*\*\* polymers, for glossy topcoats)

IT Crosslinking agents

( \*\*\*aminoplasts\*\*\*, for \*\*\*acrylic\*\*\* polymer coatings)

IT \*\*\*Aminoplasts\*\*\*

RL: MOA (Modifier or additive use); USES (Uses)

(crosslinking agents, for \*\*\*acrylic\*\*\* polymer coatings)

IT Crosslinking catalysts

(quaternary \*\*\*phosphonium\*\*\* salts, for \*\*\*acrylic\*\*\* polymer coatings)

IT 1100-88-5, \*\*\*Benzyltriphenylphosphonium\*\*\* chloride 2304-30-5,

\*\*\*Tetrabutylphosphonium\*\*\* chloride

RL: CAT (Catalyst use); USES (Uses)

(catalysts, for crosslinking of \*\*\*acrylic\*\*\* polymer coatings)

IT 140921-87-5P 140921-88-6P 140921-89-7P 140921-90-0P

RL: TEM (Technical or engineered material use); PREP (Preparation); USES

(Uses)  
(coatings, thermosetting, manuf. of)

L13 ANSWER 1 OF 1 CAPLUS COPYRIGHT 2004 ACS on STN  
 AN 1992:196342 CAPLUS  
 DN 116:196342  
 ED Entered STN: 16 May 1992  
 TI Thermosetting glossy topcoating compositions  
 IN Fukuda, Mitsuhiro; Yabuta, Motoshi; Nakao, Yasushi  
 PA Kansai Paint Co., Ltd., Japan  
 SO Jpn. Kokai Tokkyo Koho, 10 pp.  
 CODEN: JKXXAF

DT Patent  
 LA Japanese  
 IC ICM C09D133-14  
 ICS C09D133-14  
 CC 42-7 (Coatings, Inks, and Related Products)  
 FAN. CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	JP 03275780	A2	19911206	JP 1990-74806	19900324
PRAI	JP 1990-74806		19900324		
AB	<p>The title comps. comprise CO<sub>2</sub>H- and OH group-contg. ***acrylic*** resins (OH no. 40-90), epoxy- and OH group-contg. ***acrylic*** resins (OH no. 40-90), 5-30% aminoplasts, and quaternary ***phosphonium*** salts. Thus, a mixt. of 50% 30:15:15:10:30 Bu methacrylate (I)-2-ethylhexyl ***acrylate*** (II)-hydroxyethyl ***acrylate*** (III)-methacrylic acid (IV)-styrene (V) copolymer (OH no. 73) soln. 80, 50% 20:18.5:15:30:16.5 I-II-III-V-glycidyl methacrylate (VI) copolymer (OH no. 73) soln. 80, 60% melamine resin 33, Bu<sub>4</sub>P<sup>+</sup> Cl<sup>-</sup> 0.5, UV absorber 1.0, and V-VI- ***acrylic*** acid-12-hydroxystearic acid-Me methacrylate graft copolymer ***microgel*** 10 parts was coated on primed steel and cured at 140.degree. for 30 min to give a coating with good resistance to acids, water, solvents, gasohol, abrasion, and thermal cycling.</p>				
ST	<p>***aminoplast*** crosslinker coating; hydroxyethyl methacrylate copolymer coating; glycidyl methacrylate copolymer coating; ***acrylate*** copolymer coating; methacrylic acid copolymer coating; styrene copolymer coating</p>				
IT	Coating materials				
IT	( ***acrylic*** polymers, for glossy topcoats)				
IT	Crosslinking agents				
IT	(aminoplasts, for ***acrylic*** polymer coatings)				
IT	Aminoplasts				
IT	RL: MOA (Modifier or additive use); USES (Uses)				
IT	(crosslinking agents, for ***acrylic*** polymer coatings)				
IT	Crosslinking catalysts				
IT	(quaternary ***phosphonium*** salts, for ***acrylic*** polymer coatings)				
IT	1100-88-5, Benzyltriphenylphosphonium chloride 2304-30-5, Tetrabutylphosphonium chloride				
IT	RL: CAT (Catalyst use); USES (Uses)				
IT	(catalysts, for crosslinking of ***acrylic*** polymer coatings)				
IT	140921-87-5P 140921-88-6P 140921-89-7P 140921-90-0P				
IT	RL: TEM (Technical or engineered material use); PREP (Preparation); USES (Uses)				
IT	(coatings, thermosetting, manuf. of)				

=>